

SPECIFICATION

TRAPPING AREA CREATING METHOD, TRAPPING AREA CREATING
APPARATUS, AND TRAPPING AREA CREATING PROGRAM STORAGE
5 MEDIUM

BACKGROUND OF THE INVENTION

Field of the Invention

10 The present invention relates to a trapping area
creating method of creating a band-shaped trapping area
extending along the color identification boundary of an
image, a trapping area creating apparatus for creating a
trapping area, a trapping area creating program for causing
a computer to execute the trapping area creating method
15 when the trapping area creating program is incorporated
into the computer, and a trapping area creating program
storage medium storing the trapping area creating program.

Description of the Related Art

20 Generally, there is known a method of creating an
image by a multicolored printing using a plurality of
machine plates associated with a plurality of primary
colors. In the event that on an image created by such a
multicolored printing there is a color identification
boundary in which colors near two primary colors are close
25 to one another, it often brings about a blank space on the
color identification boundary owing to misregistration
among a plurality of machine plates. In view of the

foregoing, hitherto, there is performed a trapping of compensating for misregistration between machine plates by means of edging one or both of two color areas contacting with each other at a color identification boundary in which
5 colors near two primary colors are close to one another, at a band-shaped trapping area along the color identification boundary.

Recently, as a computer technology advances, it often happens that editing of an image created by a
10 multicolored printing is performed on a computer. In this case, it is troublesome for editors to severally create the trapping area. Accordingly, there is desired a trapping area creating program for automatically creating a trapping area from image data.

As a method of creating trapping area by such a
15 trapping area creating program, there is proposed, for example, a creating method in which an image is divided into a large number of small areas as a lattice, existence as to a color identification boundary is decided for each
20 small area, and the small areas associated with the color identification boundary are coupled with one another to create a band-shaped trapping area.

In order to create a band-shaped trapping area, it is necessary that an image be divided into a sufficiently
25 large number of small areas. However, dividing the image into so large number of small areas causes an amount of computation to be enormous. This involves a problem that a

creation of the trapping area is slow down.

SUMMARY OF THE INVENTION

In view of the foregoing, it is an object of the present invention to provide a trapping area creating method capable of creating a trapping area at high speed, a trapping area creating apparatus for creating a trapping area at high speed in accordance with such a trapping area creating method, a trapping area creating program for causing a computer to execute the trapping area creating method when the trapping area creating program is incorporated into the computer, and a trapping area creating program storage medium storing the trapping area creating program.

To achieve the above-mentioned object, the present invention provides a trapping area creating method comprising:

a division step of dividing an image represented in form of a combination of polygons to which colors are applied, into a plurality of image areas by a straight line passing through vertexes of the polygons;

a decision step of deciding a propriety of trapping for each pair of image areas adjacent to one another in at least one direction of predetermined two directions, with respect to the plurality of image areas wherein the image is divided; and

a trapping area creating step of creating a band-

shaped trapping area extending along a boundary of two image areas constituting a pair of image areas decided as being suitable for a trapping in said decision step.

5 It is acceptable that the trapping area creating method according to the present invention includes, as an occasion arises, other than said division step, a step of dividing the image by a straight line passing through an intersection of the sides constituting the polygon.

10 According to the trapping area creating method of the present invention, it is possible to create a trapping area even if the number of divisions for the image in the division step is kept on not many. Accordingly it is possible to create the trapping area at high speed with a computer and the like.

15 In the trapping area creating method according to the present invention as mentioned above, it is preferable that said division step divides the image using, as said straight line, straight lines extending in same directions as said predetermined two directions passing through the vertexes of the polygon, and sides of the polygon.

20 Here, it is acceptable that the division step is one in which all the sides and the straight lines as mentioned above are used unconditionally or alternatively another one in which those elements are optionally selected.

25 According to the preferable trapping area creating method as mentioned above, a direction of the straight line used for a division of the image is contrived. Thus, it is

possible to reduce the number of times of deciding propriety of trapping. As a result, it is possible to create the trapping area at high speed.

5 In the trapping area creating method according to the present invention as mentioned above, it is an aspect that said decision step typically adopts, as said predetermined two directions, an upper and lower direction and a right and left direction of the image.

10 In the trapping area creating method according to the present invention as mentioned above, it is preferable that said decision step decides the propriety of trapping in accordance with a difference between colors of two image areas constituting said pair of image areas. Decision of the propriety of trapping can be performed readily and at
15 high speed.

Further, in the trapping area creating method according to the present invention as mentioned above, it is preferable that said trapping area creating step creates, as said trapping area, an area interposed between a line
20 constituting said boundary and a line obtained when said line (first occurring) is subjected to a parallel translation. Such an area can be created readily and at high speed.

To achieve the above-mentioned object, the present
25 invention provides a trapping area creating apparatus creating a trapping area in accordance with a trapping area creating method comprising:

a division step of dividing an image represented in form of a combination of polygons to which colors are applied, into a plurality of image areas by a straight line passing through vertexes of the polygons;

5 a decision step of deciding a propriety of trapping for each pair of image areas adjacent to one another in at least one direction of predetermined two directions, with respect to the plurality of image areas wherein the image is divided; and

10 a trapping area creating step of creating a band-shaped trapping area extending along a boundary of two image areas constituting a pair of image areas decided as being suitable for a trapping in said decision step.

To achieve the above-mentioned object, the present invention provides a trapping area creating program, which causes a computer to execute a trapping area creating method comprising:

20 a division step of dividing an image represented in form of a combination of polygons to which colors are applied, into a plurality of image areas by a straight line passing through vertexes of the polygons;

25 a decision step of deciding a propriety of trapping for each pair of image areas adjacent to one another in at least one direction of predetermined two directions, with respect to the plurality of image areas wherein the image is divided; and

a trapping area creating step of creating a band-

shaped trapping area extending along a boundary of two image areas constituting a pair of image areas decided as being suitable for a trapping in said decision step,

5 when said trapping area creating program is incorporated into said computer.

To achieve the above-mentioned object, the present invention provides a trapping area creating program storage medium storing a trapping area creating program, which causes a computer to execute a trapping area creating method comprising:

10 a division step of dividing an image represented in form of a combination of polygons to which colors are applied, into a plurality of image areas by a straight line passing through vertexes of the polygons;

15 a decision step of deciding a propriety of trapping for each pair of image areas adjacent to one another in at least one direction of predetermined two directions, with respect to the plurality of image areas wherein the image is divided; and

20 a trapping area creating step of creating a band-shaped trapping area extending along a boundary of two image areas constituting a pair of image areas decided as being suitable for a trapping in said decision step,

25 when said trapping area creating program is incorporated into said computer.

Incidentally, with respect to the trapping area creating apparatus of the present invention and the

trapping area creating program of the present invention,
only the basic embodiments are shown. However, this is to
do so in order to avoid the redundancy, and it is noted
that the trapping area creating apparatus of the present
invention and the trapping area creating program of the
invention include not only the basic embodiments, but also
a various types of embodiments of the trapping area
creating apparatus and the trapping area creating program
corresponding to the above-mentioned trapping area creating
method.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a flowchart useful for understanding a
trapping area creating method according to an embodiment of
the present invention.

Fig. 2 is a view showing an example of a component
constituting an image.

Fig. 3 is an explanatory view for a segment
resolution.

Fig. 4 is a view showing an example of a
coordinate tree.

Fig. 5 is a view showing a segment resolution of a
triangular component shown in Fig. 2.

Fig. 6 is a view showing a coordinate tree of a
triangular component shown in Fig. 2.

Fig. 7 is a view showing a first step of the
procedure in which coordinate trees are merged together.

Fig. 8 is a view showing a second step of the procedure in which coordinate trees are merged together.

Fig. 9 is a view showing a third step of the procedure in which coordinate trees are merged together.

5 Fig. 10 is a view showing a fourth step of the procedure in which coordinate trees are merged together.

Fig. 11 is a view showing a fifth step of the procedure in which coordinate trees are merged together.

10 Fig. 12 is a view showing a sixth step of the procedure in which coordinate trees are merged together.

Fig. 13 is a view showing a seventh step of the procedure in which coordinate trees are merged together.

Fig. 14 is a view showing a final step of the procedure in which coordinate trees are merged together.

15 Fig. 15 is a view showing area data generated from coordinate trees.

Fig. 16 is a view showing a divided image.

Fig. 17 is a view showing an image in which an area is divided.

20 Fig. 18 is a view showing a created trapping area.

Fig. 19 is a view showing a state that trapping areas are created on all the area pairs shown in Table 4.

Fig. 20 is a view showing a first step of the procedure in which an integrated trapping area is created.

25 Fig. 21 is a view showing a second step of the procedure in which an integrated trapping area is created.

Fig. 22 is a view showing a third step of the

procedure in which an integrated trapping area is created.

Fig. 23 is a view showing a final step of the procedure in which an integrated trapping area is created.

Fig. 24 is a perspective view of a trapping area creating apparatus according to an embodiment of the present invention.

Fig. 25 is a hardware structural view of a trapping area creating apparatus according to an embodiment of the present invention.

Fig. 26 is a view showing an embodiment of a trapping area creating program and a trapping area creating program storage medium of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Embodiments of the present invention will be described with reference to the accompanying drawings.

In the following explanation, the following image data and the like are premised. That is, image data representative of an image is constructed in form of an assembly of component data, which are indicative of colored polygon. A figure constructed by a curve such as a circle is approximately expressed by a polygon. Hereinafter, it happens that a polygon represented by the component data is referred to as "component".

A plurality of polygons represented by a plurality of component data constituting the image data is involved in a relationship of the upper and lower sides. In a case

where an "upper" of polygon is overlapped with a "lower" of polygon, an external form and a color of the "upper" of polygon take priority. The component data includes coordinates of the vertexes constituting a polygon.

5 This type of image data has been utilized in various fields.

Fig. 1 is a flowchart useful for understanding a trapping area creating method according to an embodiment of the present invention.

10 Of this flowchart, step 01 to step 11, which will be described later, constitute an example of a division step referred to in the present invention.

15 Further, of this flowchart, step 13, which will be described later, corresponds to an example of a decision step referred to in the present invention.

Furthermore, of this flowchart, step 14 to step 17, which will be described later, constitute an example of a trapping area creating step referred to in the present invention.

20 Hereinafter, this flowchart will be explained in conjunction with the accompanying drawings.

First, component data, which are objects for creation of coordinates trees as will be described latter, are derived one by one from an assembly of component data constituting image data (a step 01 in Fig. 1). Here, the component data are sequentially derived from the "lower" side in accordance with the above-mentioned relationship of

25

the upper and lower sides, which is applied to the component data constituting image data.

Fig. 2 is a view showing an example of a component constituting an image.

5 An image shown in Fig. 2 consists of a rectangular component to which magenta is applied, and a triangular component to which cyan is applied. The rectangular component is the "lower" side, and the triangular component is the "upper" side. Accordingly, first, the rectangular component is derived, and then the triangular component is
10 derived. A component number for identifying a component is applied to each of the components. Here, the component number "101" is applied to the rectangular component, and the component number "102" is applied to the triangular
15 component.

Coordinates of four vertexes A1, A2, A3 and A4, which constitute the rectangle, are expressed by (xa1, ya1), (xa1, ya2), (xa2, ya2) and (xa2, ya1), respectively. Coordinates of three vertexes B1, B2 and B3, which
20 constitute the triangle, are expressed by (xb1, ya1), (xb2, yb2) and (xb3, yb2), respectively. It is noted that an X-coordinate value is larger with farther going toward the right of Fig. 2, and an Y-coordinate value is larger with farther going downwards. Paths of the components are
25 subjected to a segment resolution in accordance with those coordinate values (a step S02 in Fig. 1).

Fig. 3 is an explanatory view for a segment

resolution.

Fig. 3 shows a segment resolution of the rectangular component shown in Fig. 2.

5 The segments constituting the component are determined in accordance with the coordinate values of the vertexes including the component data. Those segments are classified into a horizontal line in which the Y-coordinate values at both the edges are equal to one another, and an upper and lower line in which the Y-coordinate values at
10 both the edges are mutually different.

In Fig. 3, in order to distinguish the upper and lower line and the horizontal line, a white circle and a black dot are applied to both the ends of a upper and lower line 202, respectively, and four-sided figures are applied
15 to both the ends of a horizontal line 201, respectively. With respect to a component constituted of three or more upper and lower lines 202, it is assumed that a supplement of the horizontal line and a division of the upper and lower line are suitably performed, and the component
20 constituted of three or more upper and lower lines 202 is converted into an assembly of components each having two upper and lower lines.

With respect to the respective upper and lower line determined in accordance with such a segment
25 resolution, an upper end point and a lower end point are extracted, and a coordinate tree, as will be described latter, is created for each component in accordance with

the extracted upper end point and lower end point (a step S03).

The black dot applied to the upper and lower lines 202 shown in Fig. 3 denotes an upper end point 203, and the white circle denotes a lower end point 204. As described above, since the coordinates of four vertexes A1, A2, A3 and A4, which constitute the rectangle, are expressed by (xa1, ya1), (xa1, ya2), (xa2, ya2) and (xa2, ya1), respectively, coordinates of two upper end points 203 are expressed by (xa1, ya1) and (xa2, ya1), respectively, and coordinates of two lower end points 203 are expressed by (xa1, ya2) and (xa2, ya2), respectively.

Fig. 4 is a view showing an example of a coordinate tree.

A coordinate tree 300 shown in Fig. 4 denotes the rectangular component shown in Fig. 2.

The coordinate tree 300 consists of a trunk 302 in which Y-coordinate values 301 range, and branches 304 in which X-coordinate values 303 associated with the Y-coordinate values 301 range. The Y-coordinate values 301 ranging to the trunk 302 and the X-coordinate values 303 ranging to the branches 304 are sorted in the order of arrows. Appended to each of the branches 304 are upper and lower sides data 305 for distinguishing the upper side point from the lower side point, and a component number 306 of a component represented by the coordinate tree 300. A pair of X-coordinate values 303 between the upper side

points ranging to one branch 304, or a pair of X-coordinate values 303 between the lower side points ranging to one branch 304 denotes a horizontal line. And, a pair of X-coordinate value 303, to which the upper and lower sides data 305 representative of the upper side point is appended, and X-coordinate value 303 existing on a branch different from the first occurring coordinate value, to which the upper and lower sides data 305 representative of the lower side point is appended, denotes a upper and lower line.

In a similar fashion to the procedures explained referring to Figs. 3 and 4, the triangular component shown in Fig. 2 is also subjected to a segment resolution so that a coordinate tree of the triangular component is created.

Fig. 5 is a view showing a segment resolution of a triangular component shown in Fig. 2. Fig. 6 is a view showing a coordinate tree of a triangular component shown in Fig. 2.

Fig. 5 shows a state in which the triangular component shown in Fig. 2 is subjected to a segment resolution into one horizontal line 201 and two upper and lower lines 202. Those two upper and lower lines 202 form a vertex angle of a triangle. Coordinates of the upper side points 203 of two the upper and lower lines 202 are expressed by (xb1, yb1). Thus, of the branches 311 of the coordinate tree 310 shown in Fig. 6, the branches, in which the same X-coordinate values xb1 are ranged, denote a

horizontal line where the length is "0".

When the step S01 to the step 03 in Fig. 1 is repeated so that coordinate trees of two or more components are created, the coordinate trees are merged together (a step S04 in Fig. 1).

Fig. 7 to Fig. 14 are views each showing the procedure in which coordinate trees are merged together.

Hereinafter, there will be explained, a procedure that a coordinate tree 310 shown in Fig. 6 is merged into the coordinate tree 300 shown in Fig. 4, referring to Fig. 7 to Fig. 14.

First, as shown in Fig. 7, Y-coordinate values shown in the trunk of the coordinate tree 310 shown in Fig. 6 are incorporated into the trunk 302 of the coordinate tree 300 shown in Fig. 4. Here, by way of an example, there is shown a procedure that the Y-coordinate value yb1 is incorporated into the trunk 302. Since the Y-coordinate value yb1 is a value between the Y-coordinate value ya1 and the Y-coordinate value ya2, the Y-coordinate value yb1 is supplemented between the Y-coordinate value ya1 and the Y-coordinate value ya2.

Next, as shown in Fig. 8, there is retrieved a pair of X-coordinate values indicative of upper and lower line exceeding the Y-coordinate value yb1. In Fig. 8, there is detected two pairs 320 of X-coordinate values each indicative of such upper and lower line. And as shown in Fig. 9, there are determined intersection points C1 and C2

of the horizontal line having the Y-coordinate value y_{b1} and the detected upper and lower lines. And a new set of the lower side point 204 and the upper side point 203 is provided at the same positions as the intersection points C1 and C2.

As shown in Fig. 10, four X-coordinate values x_{a1} , x_{a1} , x_{a2} and x_{a2} corresponding to the newly provided lower side points and the upper side points are added to the coordinate tree in form of a branch to the Y-coordinate value y_{b1} . As a result, as mentioned above, an image is divided by the horizontal line coupling between the newly provided upper side points and the horizontal line coupling between the newly provided lower side points.

Further, as shown in Fig. 11, two X-coordinate values x_{b1} and x_{b1} corresponding to the Y-coordinate value y_{b1} are extracted from the coordinate tree 310 shown in Fig. 6 and are supplemented to the coordinate tree 310 in Fig. 11. But, component numbers appended to the two X-coordinate values x_{b1} and x_{b1} thus supplemented are "102", and are different from the component numbers appended to other X-coordinate values shown in Fig. 11. That is, the supplemented two X-coordinate values x_{b1} and x_{b1} are supplemented in form of coordinate values of vertexes constituting the component of the number "102".

Thereafter, as shown in Fig. 12, X-coordinate values of branches to the Y-coordinate value y_{b1} are sorted. And as shown in Fig. 13, X-coordinate values x_{b1} and x_{b1} ,

which are the same as the X-coordinate values $xb1$ and $xb1$ supplemented in Fig. 11, are further supplemented. The component number appended to the supplemented two X-coordinate values $xb1$ and $xb1$ are "101". Those two X-coordinate values $xb1$ and $xb1$ are supplemented to the coordinate tree in form of coordinate values constituting a frame in which a rectangular component is hollowed out by a triangular component.

This procedure explained referring to Fig. 7 to Fig. 13 is executed on the Y-coordinate value $yb2$ shown in Fig. 6 too, and as shown in Fig. 14, merging of the coordinate trees is completed.

Incidentally, according to the above-mentioned explanation, there is no explanation as to a case where sides, which constitute each of a plurality of components constituting an image, intersect each other. In case of intersection of the sides, however, when the coordinate tree is merged, the intersection point of those sides is also computed. Those sides are divided at the intersection point and a new set of upper side point and lower side point is established. Further, a horizontal line passing through the intersection point suitably divides the image.

The creation and merging of the coordinate trees in the step S01 to the step S04 are repeated for each of the components constituting the image (a step S05 in Fig. 1). As a result, it is possible to obtain a coordinate tree in which all of the coordinate trees of the components

constituting the image are merged. Thus, area data representative of an area in which an image is divided is created from the merged coordinate tree (a step S06 in Fig. 1).

5 Fig. 15 is a view showing area data generated from coordinate trees.

Area data representative of polygonal area consisting of combinations of the upper and lower side lines and the horizontal lines are sequentially extracted from the upward stream side of the coordinate trees shown in Fig. 14. Here, total five area data 330 are extracted. Extraction of those area data 330 causes the image shown in Fig. 2 to be substantially divided into five areas. Appended to the extracted area data are area numbers "103", "104", "105", "106" and "107", which are for distinguish the areas represented by the area data from one another.

Fig. 16 is a view showing a divided image.

Fig. 16 shows a result that the image shown in Fig. 2 is divided into five areas such as the area numbers "103", "104", "105", "106" and "107". Horizontal lines 211 passing through vertexes B1, B2 and B3 divide the image. According to the present embodiment, all the horizontal lines passing through vertexes B1, B2 and B3 unconditionally divide the image.

25 Next, an area number table representative of a positional relation among the areas is created in accordance with the area data extracted from the coordinate

trees and then created (a step S07).

Table 1

Area Nos.	Area Nos. on upper	Area Nos. on right	Area Nos. on below
103	non	non	104,105,106
104	103	105	107
105	103	106	107
106	103	non	107
107	104,105,106	non	non

5 Table 1 shows an area number table created in accordance with the five area data 330 shown in Fig. 15. An area number column of the left end of the area number table shows numbers of areas represented by the area data 330 shown in Fig. 15. Three columns of right side of the
10 area number table show numbers of areas adjacent upward, rightward and downward with respect to the areas represented by the numbers shown in the area number column, respectively. Here, the areas adjacent upward and downward are areas adjacent upward and downward with respect to the
15 horizontal line, respectively. The area adjacent rightward is an area adjacent rightward with respect to the upper and lower line. With respect to the area of the number "105", it is processed assuming that the horizontal line of the length "0" interposed between two upper side points exists
20 at the position of the vertex against the base of the triangle.

Area information represented by the respective stage of the area number table thus created denotes a positional relation between a certain area and a peripheral

area of the certain area. The area information is derived from the area number table one by one for a stage of area information (a step S08 in Fig. 1), and it is determined as to whether there is a plurality of areas adjacent upward or downward with respect to a certain area (a step S09 in Fig. 1). For example, according to the area number table shown in Table 1, three areas exist downward the area of the number "103", and three areas exist upward the area of the number "107".

Thus, in the event that there is a plurality of areas adjacent upward or downward, the area is further divided by a vertical line extending in a vertical direction (a step S10 in Fig. 1). In the area number table shown in Table 1, the area of the number "103" and the area of the number "107" are an object of the further division, and as will be described, they are divided by the vertical line.

The above-mentioned processing of the step S08 and the step S09 is repeated on the whole area information shown in the area number table (a step S11 in Fig. 1).

Fig. 17 is a view showing an image in which an area is divided.

The area of the number "103" shown in Fig. 16 is divided into three areas by a vertical line 212 passing through the vertex B1. Appended to those three areas are area numbers "103", "108" and "111". It is noted that the area of the number "111" is "0" in area. The area of the number "107" shown in Fig. 16 is divided into three areas by vertical lines 212 passing through the vertexes B2 and B3. Appended to those three areas are area numbers "107",

"109" and "110". According to the present embodiment, of the vertical lines passing through the vertexes, the necessary minimum of vertical line is selected and is used for a division.

5 After such a division of the areas is performed, the area number table is remade.

Table 2

Area Nos.	Area Nos. on upper	Area Nos. on right	Area Nos. on below
103	Non	111	104
104	103	105	107
105	111	106	109
106	108	non	110
107	104	109	non
108	non	non	106
109	105	110	non
110	106	non	non
111	non	108	105

10 Table 2 shows one in which the area numbers table shown in Table 1 is remade after the further division of the areas. As a result of the further division of the areas, the association between the areas mutually adjacent in the upper and lower direction is given by a one-to-one
15 correspondence.

Color information representative of colors of

areas represented by the area numbers shown in the area number table thus remade is obtained in accordance with the component data and is supplemented to the area number table a step S12 in Fig. 1).

5

Table 3

Area Nos.	Colors	Area Nos. on upper	Colors	Area Nos. on right	Colors
103	Magenta	non		111	Magenta
104	Magenta	103	Magenta	105	Cyan
105	Cyan	111	Magenta	106	Magenta
106	Magenta	108	Magenta	Non	
107	Magenta	104	Magenta	109	Magenta
108	Magenta	non		non	
109	Magenta	105	Cyan	110	Magenta
110	Magenta	106	Magenta	non	
111	Magenta	non		108	Magenta

Table 3 shows an area number table in which the color information representative of colors of areas represented by the area numbers shown in Table 2 is supplemented. Color information representative of cyan is combined with the area number "105", and color information representative of magenta is combined with other than the area number "105".

15

A trapping candidate to be subjected to trapping is determined in accordance with the area number table to

which the above-mentioned color information is supplemented,
and a predetermined trapping condition, in form of an area
pair (a step S13 in Fig. 1). For each of the stages in
Table 3, it is checked as to whether a pair of an area
5 represented by the area number shown in the area number
column and an area adjacent upward the area (first
occurrence) satisfies the trapping condition. Further it
is also checked as to whether a pair of an area represented
by the area number shown in the area number column and an
10 area adjacent rightward the area (first occurrence)
satisfies the trapping condition. According to the present
embodiment, as colors of areas, only two colors of magenta
and cyan are supposed. Accordingly, there is used such a
simple trapping condition that the trapping is performed
15 when colors of the adjacent two areas are different from
each other.

Table 4

Object areas	Colors	Trapping Object	Colors
104	Magenta	105	Cyan
105	Cyan	106	Magenta
105	Cyan	111	Magenta
109	Magenta	105	Cyan

Table 4 shows area pairs satisfying the above-

mentioned simple trapping condition.

As a trapping condition other than the above-mentioned simple trapping condition, there are considered, for example, such a condition that a trapping is performed when a color difference between the mutually adjacent two areas is larger than a predetermined color difference, and such a condition that a trapping is performed when a difference in chromaticity between those two areas is larger than a predetermined value.

When the area pair as shown in Table 4 is determined, the trapping area is created in accordance with the following procedure.

First, a pair of areas as a trapping candidate is obtained (a step S14 in Fig. 1). Then, a band-shaped trapping area, which extends along the boundary of two areas constituting the area pair, is created (a step S15 in Fig. 1). As a position at which a trapping area is created, there are considered three ways of one side, another side and both sides of the boundary line of two areas adjacent to each other. Here, a trapping area is created in a condition that the trapping area is created always at one side of the magenta side. As a technique of creating a trapping area, here, there is adopted such a technique that a segment extending in parallel to the boundary line is determined, and a band-shaped area interposed between the segment and the boundary line is created in form of a trapping area.

As a color applied to the trapping area thus generated, there are considered the same color as a color of one of the two areas and neutral tints of colors of the areas. Here, the neutral tints of cyan and magenta are applied to the trapping area.

Generally, there is generated a trapping area according to the color difference between two areas mutually adjacent. For example, in the event that the color difference is large, there is created a trapping area in which an area light in color makes inroads into an area dark in color. In the event that the color difference is small, there is created a trapping area in which both the areas make inroads into one another.

Fig. 18 is a view showing a created trapping area.

According to the present embodiment, a segment extending in parallel to the boundary line is determined assuming that the boundary line is translated in parallel to any direction of four directions of the upper and lower sides and the right and left sides by a predetermined amount w . In Fig. 18, a pair of an area of a number "104" and an area of a number "105" is a trapping candidate. A boundary line 221 of those areas is subjected to a parallel translation horizontally in the left direction of the figure, so that a segment 222 having two coordinate points $(xb1-w, yb1)$, $(xb2-w, yb2)$ as its both ends is determined. And an area hatched, which is interposed between the segment 222 and the boundary line 221, is created in form

of a trapping area 223.

The above-mentioned step S14 and step S15 are repeated until all of the area pairs as the trapping candidates as shown in the Table 4 are obtained and trapping areas for all the area pairs are created (a step S16 in Fig. 1: Yes).

Fig. 19 is a view showing a state that trapping areas are created on all the area pairs shown in Table 4.

There are created three band-shaped trapping areas 223 in such a manner that the areas 223 encircle a triangular area of the center. Further, there is also created a trapping area 223 of an area "0" upward the vertex opposing to the bottom of the triangle.

The trapping areas thus created are combined so that an integrated trapping area is created (a step S17 in Fig. 1).

Fig. 20 to Fig. 23 is views showing the procedure in which an integrated trapping area is created in the step S17.

Hereinafter, there will be explained the procedure in which an integrated trapping area is created, referring to the figures.

Fig. 20 shows vertexes of a polygonal, which constitute the trapping areas 223 created in the step S14 to S16, together with coordinate values of the vertexes. A coordinate tree 340 shown in Fig. 21 is created in accordance with the coordinate values of the vertexes. As

shown in Fig. 22 with hatching, coordinate values 341 of external points constituting an external form of the integrated trapping area are extracted from the coordinate tree 340.

5 Thereafter, as shown in Fig. 23, an external form of line 232 is created in such a manner that the external points 231 represented by the extracted coordinate values are sequentially coupled, and an integrated trapping area 233, which is interposed between the external form of line 10 232 and the above-mentioned boundary line, is created as shown with hatching.

 According to the above-mentioned trapping area creating method, the number of divisions of an image is not many and an amount of arithmetic operation is also not much. 15 Thus, it is possible to create the trapping areas at high speed.

 The number of divisions of an image and a divisional condition for determining as to whether an image is to be divided (for example, a condition for determining 20 as to whether a division by the vertical line is to be performed) are not restricted to the present embodiment and can be suitably altered. Even if the number of divisions is increased as a result that the divisional condition, which is different from that in the present embodiment, is 25 adopted, the total number of the divisions is restricted to the number sufficiently not so many, and thus it is possible to create the trapping area at high speed.

Further, according to the present embodiment as mentioned above, as an example of the technique of dividing an image, there is shown the technique of the division by merging of coordinate trees. However, in the division step of the present invention, it is acceptable that an image is divided in accordance with a technique other than the technique shown in the present embodiment as mentioned above.

As to a direction in which an area adjacent to a certain area is checked in order to determine a trapping candidate, there are considered two ways of down and left, and two ways of up and left, other than two ways of up and right as mentioned above. Further, as to a divisional direction of an image, there are considered a 45-degree direction and a 135-degree direction. In the event that such a divisional direction is adopted, as a direction in which the adjacent area is checked, there are considered two ways of upper right and lower right.

Finally, there will be described an embodiment of a trapping area creating apparatus of the present invention and an embodiment of a trapping area creating program storage medium of the present invention.

Fig. 24 is a perspective view of a trapping area creating apparatus according to an embodiment of the present invention. Fig. 25 is a hardware structural view of a trapping area creating apparatus according to an embodiment of the present invention.

A trapping area creating apparatus 400 is constituted of a computer.

The trapping area creating apparatus 400 comprises, on an external appearance, a main frame unit 410, an image display unit 420 for displaying an image on a display screen 420a in accordance with an instruction from the main frame unit 410, a keyboard 430 for inputting various sorts of information to the main frame unit 410 in accordance with a key operation, and a mouse 440 for inputting an instruction according to, for example, an icon and the like, through designation of an optional position on the display screen 420a, the icon and the like being displayed on the position on the display screen 420a. The main frame unit 410 has a floppy disk mounting slot 410a for mounting a floppy disk, and a CD-ROM mounting slot 410b for mounting a CD-ROM.

The main frame unit 410 comprises, as shown in Fig. 25, a CPU 411 for executing a various types of program, a main memory 412 in which a program stored in a hard disk unit 413 is read out and developed for execution by the CPU 411, the hard disk unit 413 for saving various types of programs and data, an FD drive 414 for accessing a floppy disk 510 mounted thereon, and a CD-ROM drive 415 for accessing a CD-ROM 520 mounted thereon. These various types of elements are connected via a bus 416 to the image display unit 420, the keyboard 430 and the mouse 440.

The CD-ROM 520 stores therein a trapping area

creating program for causing the computer to operate as a trapping area producing apparatus. The CD-ROM 520 is mounted on the CD-ROM drive 415 so that the trapping area creating program, which is stored in the CD-ROM 520, is up-
5 loaded on the computer and is stored in the hard disk unit 413. The trapping area creating program thus up-loaded is developed on the main memory 412 and is executed in the CPU 411.

When the CD-ROM 520 stores an embodiment of a trapping area creating program of the present invention,
10 the CD-ROM 520 corresponds to an embodiment of a trapping area creating program storage medium of the present invention. When the trapping area creating program is up-loaded and is stored in the hard disk unit 413, the hard
15 disk unit 413, which stores therein the trapping area creating program, also corresponds to an embodiment of a trapping area creating program storage medium of the present invention. Further, when the trapping area creating program is down-loaded on the floppy disk 510, the
20 floppy disk 510, which stores therein the trapping area creating program, also corresponds to an embodiment of a trapping area creating program storage medium of the present invention.

When an embodiment of a trapping area creating
25 program of the present invention is up-loaded and executed as mentioned above, the trapping area creating apparatus 400, which operates as an embodiment of a trapping area

creating apparatus of the present invention, is implemented. Here, an operation of the trapping area creating apparatus 400 is an operation that the above-mentioned trapping area creating method is executed.

5 Fig. 26 is a view showing an embodiment of a trapping area creating program and a trapping area creating program storage medium of the present invention.

10 A storage medium 550 shown in Fig. 26 represents the floppy disk 510, the CD-ROM 520 and the hard disk unit 413 as shown in Fig. 25. The storage medium 550 stores therein a trapping area creating program 551 including a division step 552, a decision step 553 and a trapping area creating step 554.

15 The division step 552 causes the computer to execute the operation shown in the step S01 to the step S11 in Fig. 1.

 The decision step 553 causes the computer to execute the operation shown in the step S13 in Fig. 1.

20 The trapping area creating step 554 causes the computer to execute the operation shown in the step S14 to the step S17 in Fig. 1.

25 When the trapping area creating program 551 is uploaded on the computer and is executed, the computer can create a trapping area at high speed in accordance with the above-mentioned trapping area creating method.

 As mentioned above, according to the present invention, it is possible to create a trapping area at high

speed.

While the present invention has been described with reference to the particular illustrative embodiments, it is not to be restricted by those embodiments but only by the appended claims. It is to be appreciated that those skilled
5 in the art can change or modify the embodiments without departing from the scope and spirit of the present invention.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2